Composite Door Measuring Guide

For Solidor timber-core composite doors

For a doorset (door and frame), measure brick to brick in three places each way, take the **smallest** and deduct about **10mm each way**.

How to Measure

1	Measure the width at the top, middle and bottom of the opening.
2	Measure the height on the left, middle and right, from the finished floor to the lintel.
3	Side panels or glass above: measure the whole opening and sketch the layout.
4	Slab only (into an existing frame): give us the rebate size, the hinge side and hinge positions, and the lock type.
5	Hinge side and opening are always described as seen from OUTSIDE.
6	Threshold: tell us if the current threshold is level and needs to stay level.

Your Measurements

Door	Width top	Width mid	Width bottom	Height L	Height mid	Height R

Before You Order

- ☐ Doorset or slab only
- ☐ Hinge side, viewed from outside; opening in or out
- ☐ Style, glass and colour (outside and inside)
- ☐ Handle, letterplate, knocker and numerals
- ☐ Threshold: standard or low
- ☐ Side panels and toplights sketched with sizes

How Ordering Works

1	Use the supply form on the product page, or log in to the trade portal if you have a trade account.
2	We check your sizes and specification and send a written quote (trade accounts get their trade price).
3	Approve the drawing or order confirmation. **Check every size, colour, handing and glass type.** Once it is in production it cannot be changed.
4	Pay the proforma invoice. We place the order and confirm the delivery or collection date.
5	Check everything on arrival and report any damage or shortage within 48 hours, with photos.

Not sure? Send photos and rough sizes with your enquiry and we will check before anything is made. Call 0118 995 2549 or email cwgwindowcraig@gmail.com.