Internal Glass Door Measuring Guide

For Korniche steel-look internal doors and screens

Measure the opening brick to brick (or stud to stud) in three places each way, take the **smallest** and **deduct 10mm** from the width and height. That is the size you order.

How to Measure

1	Measure the width at the top, middle and bottom of the opening.
2	Measure the height on the left, middle and right, from finished floor level.
3	Deduct 10mm from the smallest width and smallest height.
4	Choose the layout: single door, French doors, door with side screen(s), or a fixed screen.
5	Say which room the door opens into and which side the hinges go.
6	Choose the glass: toughened, laminated, acoustic laminated (for kitchens and home offices), or obscure for privacy.

Your Measurements

Opening	Width top	Width mid	Width bottom	Height L	Height mid	Height R

Before You Order

- ☐ Order size = smallest measurement minus 10mm
- ☐ Layout and bar style (horizontal or grid)
- ☐ Opening direction and hinge side
- ☐ Frame colour (matt black as standard)
- ☐ Glass type
- ☐ Not a fire door location: these doors are not fire rated

How Ordering Works

1	Use the supply form on the product page, or log in to the trade portal if you have a trade account.
2	We check your sizes and specification and send a written quote (trade accounts get their trade price).
3	Approve the drawing or order confirmation. **Check every size, colour, handing and glass type.** Once it is in production it cannot be changed.
4	Pay the proforma invoice. We place the order and confirm the delivery or collection date.
5	Check everything on arrival and report any damage or shortage within 48 hours, with photos.

Not sure? Send photos and rough sizes with your enquiry and we will check before anything is made. Call 0118 995 2549 or email cwgwindowcraig@gmail.com.